




T700 FAMILY OF THERMOSTATS



700 Family

Featuring
T701i WIFI THERMOSTAT
Exclusively For Contractors

The 700 family of thermostats offers the most commonly desired features at a great value. These models are easy to use and will provide years of reliable service. With a model for nearly any system it is no surprise the 700 family is so popular.



T701 • T701i • T771



T705 • T715 • T721 • T725



T755 • T755S • T755H

Quality Has Never Been Such A Good Value



1-800-PRO1-559 (776-1559)

www.pro1iaq.com

Features of the T700 Family of Thermostats

- Extra large blue backlight screen
- Easy menu driven programming (programmable models only)
- Room temperature calibration adjustment
- 5 minute compressor delay protection (selectable on or off)
- Advanced humidification & de-humidification controls (Model # 755H)
- 4 or 6 sq inch display (depending on model)
- 5/1/1 programmable (programmable models only)
- Separate heating and cooling swing (cycle rate) adjustments
- Separate B & O terminals
- Universal sub-base
- Easy access battery compartment
- Filter change indicator (selectable on or off)
- Intuitive wake, leave, return, sleep programming icons (programmable models only)
- Easy wire color coded terminal blocks
- Wall mount or junction box
- Battery or 24V power
- Backlight button

Model #	7D 7 Day Programmable	5/1/1 5/1/1 Programmable	NP Non-programmable	Stages of Heat	Stages of Cool	Heat pump with emergency heat compatible	Compatible with Conventional Systems	Display Size (Square Inches)	Auto Changeover	Filter Change Reminder	Room Temperature Calibration	Adjustable Temperature	Programmable Swing	Adjustable Setpoint Limits	Humidity Control	Memory Type (Permanent)	Touchscreen	Warranty (Years)	Terminals	
T771			NP	0/1	0/1	•	•	4	•	•	•	•	•	•	•	•	•	•	5	R, C, W/Y, G
T755H	5/1/1	5/1/1	NP	3*	2	•	•	6	•	•	•	•	•	•	•	•	•	•	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O, H, D
T755S	5/1/1	5/1/1	NP	3*	2	•	•	6	•	•	•	•	•	•	•	•	•	•	5	
T755	5/1/1	5/1/1	NP	3*	2	•	•	6	•	•	•	•	•	•	•	•	•	•	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O
T725	5/1/1			2	1	•	•	4	•	•	•	•	•	•	•	•	•	•	5	R, C, Y, W2, E, G, B, O
T721			NP	2	1	•	•	4	•	•	•	•	•	•	•	•	•	•	5	R, C, Y, W2, E, G, B, O
T715	5/1/1			2	2	•	•	4	•	•	•	•	•	•	•	•	•	•	5	R, C, Y, Y2, W, W2, G
T705	5/1/1			1	1	•	•	4	•	•	•	•	•	•	•	•	•	•	5	Rh, Rc, C, Y, W, G, B, O
T701i			NP**	1	1	•	•	4	•	•	•	•	•	•	•	•	•	•	3	Rh, Rc, C, Y, W, G, B, O
T701			NP	1	1	•	•	4	•	•	•	•	•	•	•	•	•	•	5	Rh, Rc, C, Y, W, G, B, O

* 3 heat stages for heat pump or 2 heat stages for conventional

Specifications

The display range of temperature.....	41°F to 95°F (5°C to 35°C)
The control range of temperature.....	44°F to 90°F (7°C to 32°C)
Load rating.....	1 amp per terminal, 1.5 amp maximum all terminals combined
Display accuracy.....	± 1
Swing (cycle rate or differential).....	Heating is adjustable from 0.2°F to 2.0°F Cooling is adjustable from 0.2°F to 2.0°F
Power source.....	18 to 30 VAC, NEC Class II, 50/60 Hz for hardwire (common wire) Battery power from 2 AA Alkaline batteries
Operating ambient.....	32° to +105° (0° to +41°C)
Operating humidity.....	90% non-condensing maximum
Dimensions of thermostat.....	4.7"W x 4.4" H x 1.1"D
WIFI Module	Supporting 802.11 B/G/N Standards
Frequency.....	2.4 GHz ISM radio band

T701i WIFI Thermostat



Universal Subbase

Fast, easy upgrade from existing Pro1 thermostats.
No additional wiring necessary as long as C is connected.



Smart Grid Capable

Works with many utility incentive programs.
Learn more from your professional installer or a Pro1 representative.



Private Label

Contractor contact info displayed in mobile app
and on magnetic badge of thermostat to generate
return business.



Active Alerts

Receive alerts from anywhere.
High and low temp. limits, connection status, and more.



Google Play is a trademark of Google Inc.
Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.