



# 708 Combustion Efficiency Analyzer

The TPI 708 is an all in one instrument designed to maximize diagnostic efficiency and accuracy.

Ask about the optional A740 Infrared Printer.



4.0" w x 8.12" h x 2.25" d

## 1. Combustion Efficiency Analyzer

- Measure O<sub>2</sub> and CO
- Calculate CO<sub>2</sub>, efficiency, excess air and ratio.
- Will work with high efficiency furnaces, hot water heaters, and other combustible gas appliances.

## 2. CO Analyzer

- Measure 0-10,000 ppm CO

## 3. Differential Thermometer

- Dual input K-Type thermocouple temperature tester



Turn over for technical information and accessory part numbers.

**NOTE:** When selecting oil as fuel be sure to use the optional oil filter or reading could become erratic. Order item A773.

### 708 FEATURES

- Easy to use
- Large, easy-to-use display
- IR printer port
- Large memory capacity (holds up to 50 sets of complete test results)
- Protective rubber boot included

### 708 ACCESSORIES

CO Sensor, Oxygen Sensor, Protective Boot, Stack Probe, PVC Tubing, Water/filter trap on Stack Probe, Shoulder Strap Carrying Case, Spare Particle Filters

### 708 OPTIONAL ACCESSORIES

A740 IR Printer

A773 Sulfer Filter

## A740 Infrared Printer

- Easy to use
- Battery operated
- Self test facility
- Adjustable contrast
- Manual paper feed
- Maximum transmitting distance 16"(45cm)
- Compatible with most other combustion analyzers



3.0" w x 6.0 h x 1.75" d



# 708 Combustion Efficiency Analyzer

## TECHNICAL SPECIFICATIONS AND ACCESSORIES

### Temperature Measurement

Range	-40° to 1472°, or -40° to 800°C
Resolution	1°F or C
Accuracy (K-type)	±0.3%, ±2°F or ±1°C

### Gross/Net Efficiency

Range	0 to 100%
Resolution	0.1%

### Oxygen (O<sub>2</sub>) Measurement

Range	0 to 25%
Resolution	0.1%
Accuracy	±0.3%

### Carbon Monoxide (CO) Measurement

Range	0 to 10,000 ppm
Resolution	1 ppm
Accuracy	±5 ppm or 5%, whichever is greater

### Carbon Dioxide (CO<sub>2</sub>)

Range	0 to 25%
Resolution	0.1%
Accuracy	Calculated

### CO/CO<sub>2</sub> Ratio

Range	0 to 0.999
Resolution	0.001
Accuracy	Calculated

### Instrument Specifications

Operating Temperature Range	14° to 122°F (-10° to 50°C)
Battery	3 "AA" Alkaline Batteries
Fuels	Natural Gas, LPG, Light Oil, Heavy Oil
Display	Backlit LCD
Data Storage	50 sets of readings
Time & Date	24 Hour Real Time Clock
Dimensions	200mm x 90mm x 60mm
Weight	500g
Exhaust	Safety Spigot
Conforms To:	BS7927 (and the draft BS7967)

### ACCESSORIES

#### Standard

Flue Probe w/K-type	A770
K-Type Temperature Probe	GK11M
In-Line Filter Complete	A762
Mini Pump Protection Filter Assembly	A763
Batteries	3 x "AA" Alkaline Batteries
Protective Boot	A765
Soft Carrying Case	A768
Exhaust Spigot	A764

#### Optional

Infrared Printer	A740
PC Software	A772
IRDA-RS232C Adapter	A767
Replacement Printer Paper (10 rolls)	A746
20 Foot Flue Gas Analyzer Probe	A770-20
Oil Filter	A773

**NOTE: When selecting oil as fuel be sure to use the optional oil filter or reading could become erratic. Order item A773.**

### Test Products

#### International, Inc.

Headquarters:  
9615 SW Allen Blvd.  
Beaverton, OR 97005  
USA  
503-520-9197  
Fax: 503-520-1225  
email:  
info@tpi-thevalueleader.com

### Test Products

#### International, Ltd.

342 Bronte St. South  
Unit 9  
Milton, Ontario L9T  
5B7  
Canada  
905-693-8558  
Fax: 905-693-0888  
email:  
info@tpicanada.com

### Test Products

#### International UK Ltd.

Longley House, East Park  
Crawley, West Sussex  
RH10 6AP England  
Tel: +44 (0)1293 561212  
Fax: +44 (0)1293813465  
contactus@tpieurope.com



**Distributed By:**



To learn about the entire line of TPI products visit:

**www.tpi-thevalueleader.com**

Copyright © 2004 Test Products International, Inc. L 708-1204